



— SPECIFICATIONS

Catalog No.	Connections	Port Type		Material
		A	B	
ANPTM4 / NPTF6	M->F / 1/4" NPT -> 3/8" NPT	1/4" NPT	3/8" NPT	STS316CW

— Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	02/10		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY
DESIGN SECTION				

Website Main site : <http://www.hiflux.com>
Shopping mall : <http://www.hifluxmall.com>

3							
2							
1	ADAPTER	M->F / 1/4" NPT -> 3/8" NPT	ANPTM4/NPTF6	STS316CW	1	EA	-
ITEM	NAME OF PART	SPEC	DESCRIPTION	MATERIAL	QUANTITY FOR ONE SET	UNIT	REMARK

MATERIAL LIST FOR ONE SET

No indication chamfer 0.2-0.4 X 45°		UNIT: MM	PROJECT: ADAPTER				
General tolerance is given in KS B ISO 2768-1			TITLE: M->F / 1/4" NPT - 3/8" NPT				
NORMINAL DIM.(MM)			CLASS OF FINISH				
OVER	UNDER	TOL.	APPD BY	CHD BY	DED BY	DRW BY	WORK NO.
0.5	6	±0.1	✓ = √, 200S,	SCALE: 1:1	DRW DATE	DWG NO.	REV. NO.
6	30	±0.2	∇ = ∇, 50S,				
30	120	±0.3	∇ = ∇, 12.5S,				
120	315	±0.5	∇ = ∇, 3.2S,				
315	1000	±0.8	∇ = ∇, 0.8S,				
1000	2000	±1.2					
OVER 2000		±1.5					