



**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Orifice Size	Port Type	Material
FT10CS08	10,000	Ø9.5	H1008	STS 316CW

- Note  
1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV No.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>					
4	-	-	-	-	-		
3	SLEEVE	10,000PSI 1/2"	FA10SS08	STS 316CW	4 EA		
2	GLAND	10,000PSI 1/2"	FA10GS08	STS 316CW	4 EA		
1	CROSS	10,000PSI 1/2"	FT10CS08	STS 316CW	1 EA		
ITEM	NAME OF PART PART CODE	SPEC	Catalog No.	MATERIAL	QUANTITY FOR ONE SET	UNIT FOR ONE SET	REMARK
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°		UNIT: MM		PROJECT Low Pressure Fitting Block			
General tolerance is given in KS B ISO 2768-1				TITLE 10,000PSI 1/2" CROSS			
NOMINAL DIM.(MM)		CLASS OF FINISH		FT10CS08			
OVER	UNDER	TOL.	√ = √, 200S,	APPD BY			
0.5	6	±0.1	√ = √, 50S,	CHD BY	DED BY	DRN BY	WORK NO.
6	30	±0.2	√ = √, 12.5S,	K.Y.J	K.Y.J	K.Y.J	HI-KYJ-260823-15
30	120	±0.3	√ = √, 3.2S,	SCALE		DRN DATE	DWG NO.
120	315	±0.5	√ = √, 0.8S,	FT10CS08		FT10CS08	REV. NO.
315	1000	±0.8					
1000	2000	±1.2					
OVER 2000		±1.5					