



**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Orifice Size	Port Type	Material
FT15CS06	15,000	Ø5	H1506	STS 316CW

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV No.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
DESIGN SECTION					

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>					
4	-	-	-	-	-	-	-
3	SLEEVE	15,000PSI 3/8"	FA15SS06	STS 316CW	4	EA	-
2	GLAND	15,000PSI 3/8"	FA15GS06	STS 316CW	4	EA	-
1	CROSS	15,000PSI 3/8"	FT15CS06	STS 316CW	1	EA	-
ITEM	NAME OF PART PART CODE	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°			UNIT: MM	PROJECT: Low Pressure Fitting Block			
General tolerance is given in KS B ISO 2768-1					TITLE: 15,000PSI 3/8" CROSS		
NOMINAL DIM.(MM)			CLASS OF FINISH				
OVER	UNDER	TOL.	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$ , 200S,				
0.5	6	±0.1	$\sqrt{\text{V}}$ = $\sqrt{\text{V}}$ , 50S,				
6	30	±0.2	$\sqrt{\text{X}}$ = $\sqrt{\text{X}}$ , 12.5S,				
30	120	±0.3	$\sqrt{\text{Y}}$ = $\sqrt{\text{Y}}$ , 3.2S,				
120	315	±0.5	$\sqrt{\text{Z}}$ = $\sqrt{\text{Z}}$ , 0.8S,				
315	1000	±0.8					
1000	2000	±1.2					
OVER 2000		±1.5					
APPROVED BY				WORK NO. H-KYJ-260623-14			
DESIGN SECTION				DNG NO. FT15CS06			