



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Orifice Size	Port Type	Material
FT15ES02	15,000	Ø1.4	H1502	STS 316CW

- Note
1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com				
4	-	-	-	-	-	
3	SLEEVE	15,000PSI 1/8"	FA15SS02	STS 316CW	2 EA	
2	GLAND	15,000PSI 1/8"	FA15GS02	STS 316CW	2 EA	
1	ELBOW	15,000PSI 1/8"	FT15ES02	STS 316CW	1 EA	
ITEM	NAME OF PART PART CODE	SPEC	Catalog No.	MATERIAL	QUANTITY UNIT FOR ONE SET	REMARK
MATERIAL LIST FOR ONE SET						
No indication chamfer 0.2~0.4 X 45°		UNIT: MM	PROJECT: Low Pressure Fitting Block			
General tolerance is given in KS B ISO 2768-1				TITLE: 15,000PSI 1/8" ELBOW FT15ES02		
NOMINAL DIM.(MM)		CLASS OF FINISH		APPD BY: K.Y.J CHD BY: K.Y.J DED BY: K.Y.J DRN BY: K.Y.J WORK NO: HI-KYJ-200223-13 REV. NO.		
OVER	UNDER	TOL	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 200S,	SCALE: DRN DATE: DWG NO: FT15ES02		
0.5	6	±0.1	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 50S,			
6	30	±0.2	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 12.5S,			
30	120	±0.3	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 3.2S,			
120	315	±0.5	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 0.8S,			
315	1000	±0.8				
1000	2000	±1.2				
OVER 2000		±1.5				