



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Minimum Opeing size	Port Type	Material
FT15ES06	15,000	Ø5	H1506	STS 316CW

- Note
1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.S		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4							
3	SLEEVE	15,000PSI 3/8"	FA15SS06	STS316CW	2	EA	-
2	GLAND	15,000PSI 3/8"	FA15GS06	STS316CW	2	EA	-
1	ELBOW	15,000PSI 3/8"	FT15ES06	STS316CW	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE				FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No Indication chamfer 0.2~0.4 X 45°		UNIT: MM		PROJECT: Low Pressure Fitting Block			
General tolerance is given in KS B ISO 2768-1				TITLE: 15,000PSI 3/8" ELBOW			
NORMINAL DIM.(MM)		CLASS OF FINISH		APPD BY			
OVER	UNDER	TOL	√ = √, 200S,	CHD BY		DED BY	
0.5	6	±0.1	√ = √, 50S,	K.Y.S		DRN BY	
6	30	±0.2	√ = √, 12.5S,	K.Y.S		WORK NO.	
30	120	±0.3	√ = √, 3.2S,	K.Y.S		HI-KY8-220215-02	
120	315	±0.5	√ = √, 0.8S,	K.Y.S		DNG NO.	
315	1000	±0.8		K.Y.S		HI-KY8-220215-02	
1000	2000	±1.2		K.Y.S		SCALE	
OVER 2000		±1.5		K.Y.S		DNG DATE	
				HIFLUX ®			