



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Orifice Size	Port Type	Material
FT15TS02	15,000	Ø1.4	H1502	STS 316CW

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	09/23	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4	-	-	-	-	-	-	-
3	SLEEVE	15,000PSI 1/8"	FA15SS02	STS 316CW	3	EA	-
2	GLAND	15,000PSI 1/8"	FA15GS02	STS 316CW	3	EA	-
1	TEE	15,000PSI 1/8"	FT15TS02	STS 316CW	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY FOR ONE SET	UNIT	REMARK
PART CODE		DESCRIPTION		MATERIAL LIST FOR ONE SET			
No indication chamfer 0.2-0.4 X 45°		UNIT: MM		PROJECT: Low Pressure Fitting Block			
General tolerance is given in KS B ISO 2768-1				TITLE: 15,000PSI 1/8\"			
NORMINAL DIM.(MM)		CLASS OF FINISH		APPD BY: K.Y.J			
OVER	UNDER	TOL.	✓ = 200S, ~	CHD BY: K.Y.J			
0.5	6	±0.1	W = 12, ~	DED BY: K.Y.J			
6	30	±0.2	X = 12, ~	DRN BY: K.Y.J			
30	120	±0.3	Y = 12, ~	WORK NO. HI-KYJ-20023-02			
120	315	±0.5	Z = 12, ~	SCALE: DRN DATE			
315	1000	±0.8	✓ = 3.2S, ~	DWG NO. FT15TS02			
1000	2000	±1.2	Z = 0.8S, ~				
OVER 2000		±1.5	Z = 0.8S, ~				