



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Minimum Opeing size	Port Type	Material
FT15TS06	15,000	Ø5	H1506	STS 316CW

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.S		
REV No.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com				
4						
3	SLEEVE	15,000PSI 3/8"	FA15SS06	STS316CW	3 EA	
2	GLAND	15,000PSI 3/8"	FA15GS06	STS316CW	3 EA	
1	TEE	15,000PSI 3/8"	FT15TS06	STS316CW	1 EA	
ITEM	NAME OF PART PART CODE	SPEC	Catalog No.	MATERIAL	QUANTITY FOR ONE SET	UNIT REMARK
MATERIAL LIST FOR ONE SET						
No indication chamfer 0.2~0.4 X 45°		UNIT: MM	PROJECT Low Pressure Fitting Block			
General tolerance is given in KS B ISO 2768-1			TITLE 15,000PSI 3/8" TEE			
NORMINAL DIM.(MM)		CLASS OF FINISH	APPD BY			
OVER	UNDER	TOL	CHD BY			
0.5	6	±0.1	DED BY			
6	30	±0.2	DRN BY			
30	120	±0.3	WORK NO. HI-KY8-220215-03			
120	315	±0.5	REV. NO.			
315	1000	±0.8	SCALE			
1000	2000	±1.2	DRN DATE			
OVER 2000		±1.5	DNG NO. HI-KY8-220215-03			

√ = √, 200S, ~
 √ = √, 50S, ▽
 √ = √, 12.5S, ▽▽
 √ = √, 3.2S, ▽▽▽
 √ = √, 0.8S, ▽▽▽▽

HIFLUX®