



**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Port Type	Material	ORIFICE SIZE
FT30CS02	30,000	H3002	STS 316CW	Ø1.2

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	06/24	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>					
4	-	-	-	-	-	-	-
3	COLLAR	30,000PSI 1/8"	FA30RS02	STS 316CW	4	EA	-
2	GLAND	30,000PSI 1/8"	FA30GS02	STS 316CW	4	EA	-
1	CROSS	30,000PSI 1/8"	FT30CS02	STS 316CW	1	EA	-
ITEM	NAME OF PART PART CODE	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°			UNIT: MM		PROJECT: HIGH PRESSURE FITTING		
General tolerance is given in KS B ISO 2768-1					TITLE: 30,000PSIG 1/8" CROSS		
NOMINAL DIM.(MM)			CLASS OF FINISH		FT30CS02		
OVER	UNDER	TOL.	✓ = √	200S, ~	APPD BY	CHD BY	DED BY
0.5	6	±0.1	√ = √	50S, ▽	K.Y.J	K.Y.J	K.Y.J
6	30	±0.2	√ = √	12.5S, ▽▽	DRN BY	WORK NO.	REV. NO.
30	120	±0.3	√ = √	3.2S, ▽▽▽	K.Y.J	HI-KYJ-200624-01	
120	315	±0.5	√ = √	0.8S, ▽▽▽▽	SCALE	DRW NO.	
315	1000	±0.8			DRN DATE	FT300802	
1000	2000	±1.2					
OVER 2000		±1.5					
				<b>HIFLUX</b> ®			