



**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Port Type	Material	Orifice Size
FT30CS16	30,000	H3016	STS 316CW	Ø11.1

**- Note**

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>					
4	-	-	-	-	-	EA	-
3	COLLAR	30,000psi 1"	FA30RS16	STS 316CW	4	EA	-
2	GLAND	30,000psi 1"	FA30GS16	STS 316CW	4	EA	-
1	CROSS	30,000psi 1"	FT30CS16	STS 316CW	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE				FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°			UNIT: MM	PROJECT MEDIUM PRESSURE FITTING BLOCK			
General tolerance is given in KS B ISO 2768-1					TITLE 30,000PSI 1" CROSS		
NORMINAL DIM.(MM)			CLASS OF FINISH		FT30CS16		
OVER	UNDER	TOL.	√ = R	200S,	APPD BY	CHD BY	DED BY
0.5	6	±0.1	√ = 12/	50S,	K.Y.J	K.Y.J	DRN BY
6	30	±0.2	√ = 12/	12.5S,			K.Y.J
30	120	±0.3	√ = 12/	3.2S,	SCALE	DRN DATE	WORK NO.
120	315	±0.5	√ = 12/	0.8S,			H-KYJ-200824-02
315	1000	±0.8	√ = 12/				REV. NO.
1000	2000	±1.2	√ = 12/				
OVER 2000		±1.5	√ = 12/				FT30CS16
				<b>HIFLUX</b> ®			