



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port Type	Material	ORIFICE SIZE
FT30TS02	30,000	H3002	STS316CW	Ø1.2

- Note
1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	08/08	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com				
4	-	-	-	-	-	-
3	COLLAR	30,000PSI 1/8"	FA30RS02	STS 316CW	3	EA
2	GLAND	30,000PSI 1/8"	FA30GS02	STS 316CW	3	EA
1	TEE	30,000PSI 1/8"	FT30TS02	STS 316CW	1	EA
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT
	PART CODE	DESCRIPTION			FOR ONE SET	REMARK
MATERIAL LIST FOR ONE SET						
No indication chamfer 0.2-0.4 X 45°		UNIT: MM	PROJECT HIGH PRESSURE FITTING			
General tolerance is given in KS B ISO 2768-1			TITLE 30,000PSIG 1/8" TEE			
NORMINAL DIM.(MM)			FT30TS02			
OVER	UNDER	TOL.	CLASS OF FINISH			
0.5	6	±0.1	✓ = 200S, ~			
6	30	±0.2	W = 125, 50S, ▽			
30	120	±0.3	X = 125, 12.5S, ▽			
120	315	±0.5	Y = 3.2S, ▽			
315	1000	±0.8	Z = 0.8S, ▽			
1000	2000	±1.2	Z = 0.8S, ▽			
	OVER 2000	±1.5	Z = 0.8S, ▽			
APPD BY	CHD BY	DED BY	DRN BY	WORK NO.	REV. NO.	
	K.Y.J	K.Y.J	K.Y.J	HI-KYJ-200823-03		
SCALE	DRN DATE	DWG NO.	FT30TS02			