






- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port type	Orifice Size(Ø)	Material
NV15RS02-A	15,000	H1502	1.4	STS316CW

- Note

1. All dimensions for reference only and subject to change.

REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY
0	FOR APPROVAL	/		
DESIGN SECTION				

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
3	SLEEVE	15,000PSI 1/8"	FA15S802	STS316CW	2	EA	-
2	GLAND	15,000PSI 1/8"	FA15G802	STS316CW	2	EA	-
1	NEEDLE VALVE	15,000PSI 1/8"	NV15RS02-A	-	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
PART CODE		DESCRIPTION		FOR ONE SET			
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°		UNIT: MM		PROJECT			
General tolerance is given in KS B ISO 2768-1				LOW PRESSURE NEEDLE VALVE			
NORMINAL DIM.(MM)		CLASS OF FINISH		TITLE			
OVER	UNDER	TOL.		NEEDLE VALVE ANGLE			
0.5	6	±0.1	✓ = √, 200S, ~	15,000PSIG 1/8"			
6	30	±0.2	✓ = √, 50S, ▽	APPRO BY			
30	120	±0.3	✓ = √, 12.5S, ▽	CHD BY	DET BY	DRN BY	WORK NO.
120	315	±0.5	✓ = √, 3.2S, ▽	KY.J	KY.J	KY.J	HK-KY-A-230330-03
315	1000	±0.8	✓ = √, 0.8S, ▽	SCALE	DRN DATE	DWG NO.	REV. NO.
1000	2000	±1.2	✓ = √, 0.8S, ▽	1:1	03, 2023	NV15RS02-A	0
OVER 2000		±1.5		HIFLUX®			