



Website		Main site : http://www.hiflux.com Shopping mail : http://www.hifluxmall.com					
3	SLEEVE	15,000PSI 1/8"	FA15S802	STS316CW	3	EA	-
2	GLAND	15,000PSI 1/8"	FA15G802	STS316CW	3	EA	-
1	NEEDLE VALVE	15,000PSI 1/8"	NV15V802-T	STS316CW	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
PART CODE		DESCRIPTION		FOR ONE SET			
MATERIAL LIST FOR ONE SET							
No Indication chamfer 0.2~0.4 X 45°		UNIT: MM		PROJECT			
General tolerance is given in K S B ISO 2788-1				LOW PRESSURE NEEDLE VALVE			
NOMINAL DIM.(MM)		CLASS OF FINISH		TITLE			
OVER	UNDER	TOL.		NEEDLE VALVE 3WAY/2ON			
0.5	6	±0.1	✓ =  12.5Ra, ~	15,000PSIG 1/8"			
6	30	±0.2	√ =  50Ra, ▽	APPD BY	CHD BY	DED BY	DRN BY
30	120	±0.3	√ =  12.5Ra, ▽	K.T.J	K.T.J	K.T.J	K.T.J
120	315	±0.5	√ =  3.2Ra, ▽	SCALE		DRN DATE	DWG NO.
315	1000	±0.8	√ =  0.8Ra, ▽	1:1		09, 2023	16V19803-T
1000	2000	±1.2					
OVER 2000		±1.5					

HIFLUX®