



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port type	Orifice Size(Ø)	Material
NV20VS06-S	20,000	H2006	5.5	STS16CW

- Note
 1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	/			
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com							
3	COLLAR	20.000PSI 3/8"	FA20RS06	STS304CW	2	EA	-		
2	GLAND	20.000PSI 3/8"	FA20GS06	STS304CW	2	EA	-		
1	NEEDLE VALVE	20.000PSI 3/8"	NV20VS06-S	-	1	EA	-		
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK		
PART CODE		DESCRIPTION		MATERIAL		FOR ONE SET			
MATERIAL LIST FOR ONE SET									
No indication chamfer 0.2-0.4 X 45°		UNIT: MM		PROJECT MEDIUM PRESSURE NEEDLE VALVE					
General tolerance is given in KS B ISO 2768-1				TITLE NEEDLE VALVE STRAIGHT					
NORMINAL DIM.(MM)		CLASS OF FINISH		20,000PSIG 3/8"					
OVER	UNDER	TOL.	CLASS OF FINISH	APPD BY	CHD BY	DED BY	DRN BY	WORK NO.	REV. NO.
0.5	6	±0.1	√ = √, 200S, ~						
6	30	±0.2	√ = √, 50S, ▽						
30	120	±0.3	√ = √, 12.5S, ▽						
120	315	±0.5	√ = √, 3.2S, ▽						
315	1000	±0.8	√ = √, 0.8S, ▽						
1000	2000	±1.2							
OVER 2000		±1.5							
				HIFLUX ®					