



Website		Main site : http://www.hiflux.com Shopping mail : http://www.hifluxmail.com					
3	COLLAR	60,000PSI 3/8"	F40R806	STS316CW	3	EA	-
2	GLAND	60,000PSI 3/8"	F40G806	STS316CW	3	EA	-
1	NEEDLE VALVE	60,000PSI 3/8"	NV80V/S06-T	-	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
PART CODE		DESCRIPTION		FOR ONE SET			
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2-0.4 X 45°		UNIT: MM		PROJECT HIGH PRESSURE NEEDLE VALVE			
General tolerance is given in KS B ISO 2768-1				TITLE NEEDLE VALVE 3WAY 20N			
NOMINAL DIM.(MM)		CLASS OF FINISH		60,000PSIG 3/8"			
OVER	UNDER	TOL.	✓ = 0.05, 200S, 	APPD BY	CHD BY	DED BY	DRN BY
0.5	6	±0.1	✓ = 0.05, 200S, 	K.Y.J	K.Y.J	K.Y.J	K.Y.J
6	30	±0.2	✓ = 0.05, 200S, 	SCALE		DRN DATE	WORK NO.
30	120	±0.3	✓ = 0.05, 200S, 	1:1		08, 2024	H-KYJ-346208-02
120	315	±0.5	✓ = 0.05, 200S, 				REV.
315	1000	±0.8	✓ = 0.05, 200S, 				H-KYJ-346208-02
1000	2000	±1.2	✓ = 0.05, 200S, 				DRW NO.
OVER 2000		±1.5	✓ = 0.05, 200S, 				NV80V/S06-T
			✓ = 0.05, 200S, 	HIFLUX 			