



— SPECIFICATIONS

Catalog No.	Pressure Range(Psi)		Orife Size(ø)	Port Type		Material
	Minimum	Maximum		Inlet	Outlet	
RV20FAS04-1	10,000	20,000	1.8	H2004	1/4"NPT	STS316CW

— Note
1. All dimensions for reference only and subject to change.

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
3	COLLAR	20,000 Psi 1/4"	FA20RS04	STS304CW	1	EA	-
2	GLAND	20,000 Psi 1/4"	FA20GS04	STS304CW	1	EA	-
1	RELIEF VALVE	10,000 - 20,000 Psi	RV20FAS04-1	STS316CW	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE	DESCRIPTION			FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2-0.4 X 45°		UNIT: MM		PROJECT: Relief Valve Field Adjustable			
General tolerance is given in KS B ISO 2768-1				TITLE: Relief Valve			
NORMINAL DIM.(MM)		CLASS OF FINISH		APPD BY: CHD BY: DED BY: DRW BY: WORK NO. REV. NO.			
OVER	UNDER	TOL.	$\sqrt{\text{ }}$ = $\sqrt{\text{ }}$, 200S, \sim $\sqrt{\text{ }}$ = $\sqrt{\text{ }}$, 50S, ∇ $\sqrt{\text{ }}$ = $\sqrt{\text{ }}$, 12.5S, $\nabla\nabla$ $\sqrt{\text{ }}$ = $\sqrt{\text{ }}$, 3.2S, $\nabla\nabla\nabla$	SCALE: 1:1 DRW DATE: DWG NO.			
0.5	6	±0.1					
6	30	±0.2					
30	120	±0.3					
120	315	±0.5					
315	1000	±0.8					
FOR APPROVAL		DRAWING REVIEWED BY APPROVED BY					

0	FOR APPROVAL			
REV		DRAWING	REVIEWED BY	APPROVED BY