



- SPECIFICATIONS

Catalog No.	Pressure Range(PSI)		Orife Size(Ø)	Port Type		Material
	Minimum	Maximum		Inlet	Outlet	
RV20FAS04-2	10,000	20,000	1.8	H2004	1/4"NPT	STS316CW

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
3	COLLAR	20,000 PSI 1/4"	FA20RS04	STS316CW	2	EA	-
2	GLAND	20,000 PSI 1/4"	FA20GS04	STS316CW	2	EA	-
1	RELIEF VALVE	10,000 - 20,000 PSI	RV20FAS04-2	STS316CW	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
PART CODE		DESCRIPTION		FOR ONE SET			REMARK
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°		UNIT: MM		PROJECT: Relief Valve Field Adjustable			
General tolerance is given in KS B ISO 2768-1		NORMINAL DIM.(MM)		TITLE: Relief Valve			
OVER	UNDER	TOL.	CLASS OF FINISH				
0.5	6	±0.1	√ = Ra, 200S,	APPD BY: K.Y.J			
6	30	±0.2	√ = Ra, 50S,	CHD BY: K.Y.J			
30	120	±0.3	√ = Ra, 12.5S,	DED BY: K.Y.J			
120	315	±0.5	√ = Ra, 3.2S,	DRN BY: K.Y.J			
315	1000	±0.8	√ = Ra, 0.8S,	WORK NO. HI-KYJ-200226-01			
1000	2000	±1.2		SCALE: 1:1			
OVER 2000		±1.5		DRN DATE: 02.2008			
				DWG NO. RV20FAS04-2-00-00			
				HIFLUX ®			

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION