



**- SPECIFICATIONS**

Catalog No.	Port Type		BODY Material
	Inlet	Outlet	
SH11S02	H1102	3/8"NPT	STS316CW

**- Note**

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	11/06	L.S.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
DESIGN SECTION					

<b>Website</b>		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>								
3	Sleeve	11,000 psi 1/8"	FA11SS02	STS 304CW	1	EA	-			
2	Gland	11,000 psi 1/8"	FA11GS02	STS 304CW	1	EA	-			
1	Safety Head	11,000 psi 1/8"	SH11S02	STS 316CW	1	EA	-			
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK			
PART CODE		DESCRIPTION		FOR ONE SET		REMARK				
MATERIAL LIST FOR ONE SET										
No indication chamfer 0.2-0.4 X 45°			UNIT: MM		PROJECT					
General tolerance is given in KS B ISO 2768-1					<b>SAFETY HEAD</b>					
NORMINAL DIM.(MM)					TITLE					
					<b>11,000PSI 1/8"</b>					
OVER	UNDER	TOL.	CLASS OF FINISH							
0.5	6	±0.1	√ = √, 200S, ~							
6	30	±0.2	√ = √, 50S, ▽							
30	120	±0.3	√ = √, 12.5S, ▽							
120	315	±0.5	√ = √, 3.2S, ▽							
315	1000	±0.8	√ = √, 0.8S, ▽							
1000	2000	±1.2								
OVER 2000		±1.5								
				APPD BY		CHD BY	DED BY	DRN BY	WORK NO.	REV. NO.
				SCALE		DRN DATE		DWG NO.		
<b>HIFLUX</b> ®										